Material Safety Data Sheet



Zep Inc. 1310 Seaboard Industrial Blvd. Atlanta, GA 30318 1-877-I-BUY-ZEP (428-9937) www.zep.com Section 1. Chemical Product and Company Identification

Product name ZEP 65

Product use Aerosol Cleaner

Product code 0037

Date of issue 07/22/08 Supersedes 01/10/06

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

INFOTRAC: (877) 541-2016 Toll Free - All Calls

Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded

In the District of Columbia (202) 483-7616

Printing date: 07/22/08 Prepared By

Compliance Services

1420 Seaboard Industrial Blvd.

Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

WARNING!

CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects Routes of Entry Dermal contact. Eye contact. Inhalation.

Eyes Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin May cause skin irritation. May be harmul if absorbed through the skin. May cause allergic

reactions in certain individuals. Skin inflammation is characterized by itching, scaling, or

reddening.

Inhalation Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory

irritation. Can cause central nervous system (CNS) depression.

Ingestion May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause

damage.

Chronic effects Prolonged or repeated contact may dry skin and cause irritation. Overexposure of this product by

inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Contains material which may cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, eyes, central nervous system (CNS), ears.

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients MONOETHANOLAMINE; 2-aminoethanol; MEA 141-43-5 1 - 5 D-LIMONENE; orange distillate; citrus terpene; cyclohexene, 1-methyl-4-(1-methylethenyl)-, 5989-27-5 1 - 5 DIETHYLENE GLYCOL MONOBUTYL ETHER; 2-(2-butoxyethoxy)-ethanol; butyl carbitol 112-34-5 1 - 5 PROPYLENE GLYCOL; 1,2-dihydroxypropane,1,2-propanediol 57-55-6 1 - 5 ALCOHOLS, C9-11, ETHOXYLATED; linear primary alcohol ethoxylate 68439-46-3 <3 HYDROCARBON PROPELLANT; blend of propane & isobutane 75-28-5; 74-98-6 1 - 10

Page: 1/4

Product code 0037 Material Safety Data Sheet Product Name ZEP 65

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and

remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact Flush contaminated skin with plenty of water. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be

kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink.

National Fire Protection Association (U.S.A.)

Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point Closed cup: 28.3°C (82.9°F)

Flammable Limits Not available.

Flammability Non-flammable. (CSMA Method)

Fire hazard CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and

the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers

may be propelled from a fire at high speed.

Fire-Fighting Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to

Procedures fire with water. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame

or any other ignition source. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash

contaminated clothing before reusing. Wash thoroughly after handling.

Storage CONTENTS UNDER PRESSURE. Do not puncture, incinerate or store the container at temperatures above 49°C

(120°F) or in direct sunlight. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Product name Exposure limits

HYDROCARBON PROPELLANT; blend of propane & isobutane ACGIH TLV / OSHA PEL (United States). Notes: Propane

TWA: 1000 ppm 8 hour(s).

MONOETHANOLAMINE; 2-aminoethanol; MEA OSHA PEL / ACGIH TLV (United States).

TWA: 3 ppm 8 hour(s).

OSHA /ACGIH (United States).

STEL: 6 ppm 15 minute(s).

Manufacturer (United States).

DIETHYLENE GLYCOL MONOBUTYL ETHER; 2-(2butoxyethoxy)-ethanol; butyl carbitol

PROPYLENE GLYCOL 12 dibutoxyethoxy

PROPYLENE GLYCOL; 1,2-dihydroxypropane,1,2-propanediol AIHA WEEL (United States). TWA: 10 mg/m³ 8 hour(s).

Personal Protective Equipment (PPE)

Safety glasses.

Eyes

Body Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering

controls to keep the airborne concentrations of vapors below their respective

occupational exposure limits.

Section 9. Physical and Chemical Properties

Physical State Liquid. [Aerosol.]

PH Not applicable

Boiling Point Not determined.

Solubility Not determined.

Specific Gravity 1.004

Color Clear. Colorless to light yellow.

Odor Citrus

Vapor Pressure Not determined.

Vapor Density Not determined.

Evaporation Rate Not determined.

VOC (Consumer) 92 (g/l). 0.76 lbs/gal (9.2%)

Page: 2/4

Product code 0037 Material Safety Data Sheet Product Name ZEP 65

Section 10. Stability and Reactivity

Stability and Reactivity

The product is stable.

In a constant of the little constant of the l

Incompatibility Keep away from heat, sparks and flame. Reactive or incompatible with the following materials:

oxidizing materials.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information

Acute Toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Monoethanolamine	LD50 Dermal	Rabbit	>1000 mg/kg	-
	LD50 Oral	Rat	1720 mg/kg	-
Diethylene Glycol Monobutyl Ether	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	5660 mg/kg	-
	LD50 Oral	Mouse	2400 mg/kg	-
Propylene Glycol	LD50 Dermal	Rabbit	208 mg/kg	-
	LD50 Oral	Mouse	240 mg/kg	-
	LD50 Oral	Dog	260 mg/kg	-
	LD50 Oral	Rat	200 mg/kg	-
Ethoxylated Alcohols	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-

Section 12. Ecological Information

Environmental Effects

No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations

Waste Information

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Consumer commodity ORM-D			
IMDG Class	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information

U.S. Federal Regulations

SARA 313 toxic chemical notification and release reporting:

Product name

Diethylene Glycol Monobutyl Ether

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65 No products were found.

Product code 0037 **Material Safety Data Sheet** Product Name ZEP 65

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.